



Video Peephole Door Camera



PH35 Price: \$199.95

- **Adjustable to Multiple Standard doors width**
 - **1/3" CCD image sensor**
 - **480 TV Lines**
 - **0.1 Lux**
 - **1.7mm Super Wide Angle Lens**
 - **DC12V**
 - **1 year parts and labor warranty**
 - *** Bracket and Lens Not Included**
-
- Adjustable to Multiple Standard doors width
 - Pick-up device: 1/3" CCD image sensor
 - Picture elements : EIA/NTSC: 512 H x 492 V - CCIR/PAL: 512 H x 582 V
 - Note: PAL only available as special order.
 - Horizontal resolution: 480 TVL
 - Minimum Illumination: 0.1 Lux
 - Horizontal Sync. frequency: EIA/NTSC: 15.734 KHZ - CCIR/PAL: 15.625 KHZ
 - Vertical frequency : EIA/NTSC: 60 HZ - CCIR/PAL: 50 HZ
 - Clock frequency: EIA/NTSC: 19.0699 MHZ - CCIR/PAL: 18.9375 MHZ
 - Lens: 1.7mm Super Wide Angle Lens
 - Video output: 1Vp-p , 75 Ohms
 - Gamma: 0.45
 - Power supply : DC12V
 - Power Consumption: 150 mA
 - Storage Temperature : -30C ~ 60C
 - Operation Temperature : -10C ~ 45C

• * Bracket and Lens Not Included