



Single channel 2400 metre Twisted Pair TX



W102T Price: \$56.95

- **Single channel 2400 metre Twisted Pair TX**

Video Input (BNC Connector) : 1Vp-p 75W

Video Input (RCA Connector) : 2Vp-p 10KW

DC Output for Motion Sensor : DC12V, 50mA (max)

Sensor Input : Bypass

DC Output for Camera : DC 12V regulated, 300mA (Max)

Power Consumption: 40mA

Dimensions : 88 x 62 x 24mm

W102T	W102T
VIDEO INPUT	1Vp-p, 75W (BNC Connector)
AUDIO INPUT	2Vp-p, 10KW (RCA Connector)
DC OUTPUT FOR MOTION SENSOR	DC12V, 50mA (max)
SENSOR INPUT	Bypass
DC OUTPUT FOR CAMERA	DC12V Regulated, 300mA (max)
POWER CONSUMPTION	40mA
DIMENSIONS	88 x 62 x 24mm
W102R	W102R
VIDEO OUTPUT	1Vp-p, 75W (BNC Connector)
VIDEO OUTPUT PORT	2
AUDIO INPUT	2Vp-p, 10KW (RCA Connector)
POWER INPUT	DC12V @80ma
Video Gain Selection	Select 1 0~300M Select 2 300~600M Select 5,1 1500~1800M
Video Gain Selection	Select 3 600~900M Select 4 900~1200M Select 5,2 1800~2100M
Video Gain Selection	Select 5 1200~1500M Select 5,3 2100~2400M
RECOMMENDED CABLE	CAT-5 UTP Cable 4 pair (24AWG,

DIMENSIONS

22AWG, 20AWG)
88 x 62 x 24mm

W102T
VIDEO INPUT
AUDIO INPUT
DC OUTPUT FOR MOTION SENSOR
SENSOR INPUT
SENSOR INPUT
DC OUTPUT FOR CAMERA
POWER CONSUMPTION
DIMENSIONS
W102R
VIDEO OUTPUT
VIDEO OUTPUT PORT
AUDIO INPUT
POWER INPUT
Video Gain Selection

W102T
1Vp-p, 75W (BNC Connector)
2Vp-p, 10KW (RCA Connector)
DC12V, 50mA (max)
Bypass
DC12V Regulated, 300mA (max)
40mA
88 x 62 x 24mm
W102R
1Vp-p, 75W (BNC Connector)
2
2Vp-p, 10KW (RCA Connector)
DC12V @80ma
Select 1 0~300M Select 2
300~600M Select 5,1
1500~1800M

Video Gain Selection

Select 3 600~900M Select 4
900~1200M Select 5,2
1800~2100M

Video Gain Selection

Select 5 1200~1500M Select 5,3
2100~2400M

RECOMMENDED CABLE

CAT-5 UTP Cable 4 pair (24AWG,
22AWG, 20AWG)

DIMENSIONS

88 x 62 x 24mm

